

Bidpond Setup Guide

Bigpond Setup Guide

This guide will take you through the steps required to configure your router to connect to the Bigpond Mobile Broadband Network.

Ensure that your Mobile Broadband USB modem is compatible with the NF5 by checking the compatibility list at:

http://media.netcomm.com.au/public/assets/file/0004/33673/3G-Compatibility-List.pdf

Ensure that your Mobile Broadband USB modem is working by testing it directly on your computer before plugging it in to the NF5 and proceeding with this guide.

1. Navigate to <u>http://192.168.20.1</u> in a web browser using **admin** as both the username and password when prompted.

(-) (-) (2) http://192.168.20.1/	,Q - ⊠ ¢	🖉 Basic Login 🗙 🕅 🕅 🖈
🚔 NetCommWireless	Status	Gigabit WiFi Router
	Login	Username admin Password •••••
		Login Clear
ی فو فو فو فو فو فو دو فو دو فو فو فو دو فو دو فو دو فو دو فو دو		

2. If prompted by the First-time Setup Wizard, click on No thanks, take me to the Basic interface



For most post-paid Bigpond Mobile Broadband connections, refer to the Basic Bigpond setup:



- 3. Ensure that the **SIM Status** is **SIM OK**. This means that the Mobile Broadband USB has been connected properly.
- 4. Select the **Mobile Broadband** tab at the left hand side.
- 5. In the **Country** field, select the country you are in. (e.g. Australia)
- 6. In the **Service Provider** field, select **Bigpond**. The APN field will automatically populate itself.
- 7. In the **APN** field, ensure that **Telstra.bigpond** is typed.
- 8. In the **Username** field, type in your Bigpond e-mail address. (e.g. abc@bigpond.com)
- 9. In the **Password** field, type in the password for your Bigpond account.
- 10. Keep the **PIN** field blank unless instructed by Bigpond.
- 11. Click on Save and apply the changes.
- 12. A **Saved!** status would appear at the bottom of the page and you will get internet access within 5 minutes.

If you still do not get internet access or if your Bigpond connection requires more configurations, refer to the advanced Bigpond Mobile Broadband setup:

13. Click **Switch to advanced view** at the bottom of the page to access the advanced configuration.

NetCommWireless		Gigabit WiFi Router		
		WAN IP Address :	0.0.0.0	
		3G Status :	Connecting	
	Vireless	3G Signal Strength :	48%	
		VoIP Status :	Unregistered	
	Mobile Broadband			
	WAN			
ک اور				
		Switch to advanced view		

14. Select the **Network Setup** menu and click the second **Network Setup**.

Gigabit WiFi Router - NF5				Switch to basic view			
Status	Network Setup	Forwarding Rules	►Security Settings	►Advanced Settings	VoIP Settings	►NAS Settings	►Toolbox
	Network Setup						
	DHCP Server						
// IPv4 System	Wireless						
	Change Password			WAN Status		Sidenc	ote

For steps 15 – 28, refer to the image below

Gigabit WiFi Router - NF5				u]])-	• NetCommWireless		Switch to basic view	
atus	▶Network Setup	Forwarding Rules	►Security Settings	Advanced Settings	►VolP Settings	►NAS Settings	►Toolbox	
	ltem				Setting			
WAN Interfa	ce		Mobile Broa	idband 🗸				
Country			Australia	~]			
Service Prov	vider		Bigpond	~				
APN			Telstra.bigpo	nd				
PIN Code				(optional))			
Dial Number	r		*99#					
Username			abc@bigpon	d.com (optional))			
Password			••••	(optional))			
Authenticati	on Type		● Auto ○ P	АР О СНАР				
Primary DN	S			(optional))			
Secondary [ONS			(optional))			
Connection	Control		Auto Recon	nect (always-on) 🗸				
Allowed Cor	nnection Time		Always C	By Schedule				
MTU			0 (0	s auto)				
Keep Alive			Disable LCP Echo Interval Max. Failure Ping Rem Host IP Interval 60	Request 10 second Time 3 times obte Host seconds	ls			
Multicast			Disable 🗸]				
IGMP Snoo	ping		Enable					
			Sav	e Undo				

- 15. In the **WAN Interface**, select **Mobile Broadband**.
- 16. In the **Country** field, select the country you are in. (e.g. Australia)
- 17. In the **Service Provider** field, select **Bigpond**. The APN field will automatically populate itself.
- 18. In the **APN** field, ensure that **Telstra.bigpond** is typed.
- 19. Keep the **PIN** field blank unless instructed by Bigpond.
- 20. In the Dial Number field, type in *99#
- 21. In the **Username** field, type in your Bigpond e-mail address. (e.g. abc@bigpond.com)
- 22. In the **Password** field, type in the password for your Bigpond account.
- 23. In the Authentication Type field, select Auto.
- 24. Keep the **Primary DNS** and **Secondary DNS** fields blank unless otherwise stated by Bigpond.
- 25. In the Connection Control field, select Auto Reconnect (always-on).
- 26. In the Allowed Connection Time, select Always.
- 27. In the Keep Alive field, select Disable unless otherwise stated by Bigpond.
- 28. Click on the **Save** button and there will be internet access within 5 minutes.