


NP7032 Wireless LAN PCMCIA



SPEED, SECURITY & FREEDOM!

NetComm's Wireless LAN PCMCIA adaptor is part of the sophisticated NetComm Wireless LAN system

All you need to maintain full LAN services is a NetComm Access Point base station (sold separately) connected to your Ethernet Network and this card installed in a Type II PCMCIA slot in your Notebook.

Alternatively you can configure a Peer-to-Peer network connection with another Notebook PC, which has an 11Mbps Wireless LAN adaptor – the freedom is yours.

NetComm ensures compatibility with other Wireless products by adopting the International interface standard for Wireless Networking – 11Mbps IEEE802.11b.

To ensure your added security and privacy, NetComm has integrated the latest 64 and 128-bit WEP encryption technology to make sure your data remains on your LAN and does not end up in the wrong hands.

CHECK THESE GREAT FEATURES

- Connect your Notebook PC to a wireless LAN with this 32Bit PC Card
- IEEE 802.11b Direct Sequence Standard Compliant
- Dynamic data rate scaling at 11, 5.5, 2 and 1 Mbps
- 64 and 128-bit Wired Equivalent Privacy (WEP) data encryption for security
- Integrated multi-path microstrip dual diversity antenna
- Supports Windows® 98, 2000, ME, XP



NP7032 Wireless LAN PCMCIA

TECHNICAL SPECIFICATIONS

Network Standard

IEEE 802.11b

Radio Data Rate

11/5.5/2/1Mbps – auto fall back

Wireless Medium

Direct Sequence Spread Spectrum (DSSS)

Frequency Band

2.4GHz Frequency Band

Modulation Technique

DBPSK@1Mbps, DQPSK@2Mbps, CCK@5.5Mbps & 11Mbps

Voltage Required: 5 V

Wired Equivalent Privacy (WEP)

64-bit data encryption 128-bit data encryption

Antenna

Integrated multi-path microstrip dual diversity antenna.

Receive Sensitivity (8% PER)

8odBm@11Mbps 87dBm@2Mbps

Max. Output Power 13dBm

Operating Environment

Temperature:

0~55 (OPERATING)

-20~75 (STORAGE)

Humidity (non-condensing):

10~90% RH

OPERATING RANGE

Indoor environment:

11Mbps 35 metres 5.5Mbps 69 metres 2Mbps 80 metres 1Mbps 100 metres

Outdoor environment:

11Mbps 100 metres
5.5Mbps 200 metres
2Mbps 250 metres
1Mbps 300 metres
Dependent upon environment

CERTIFICATION

• C-tick (Australia)

DIMENSIONS

- (L x W x H): 100 x 54 x 5mm
- Weight: 40g

SYSTEM INTERFACE

• PCMCIA, PC Card type II

SYSTEM REQUIREMENTS

- PCMCIA Type II slot
- Windows® 98/2000/ME/XP

DRIVER SUPPORT

Windows® 98/2000/ME/XP



PACKAGE CONTENTS

- NP7032 Wireless LAN PCMCIA Adaptor
- Driver and utility CD
- Quick Start User Guide and Installation Guide

3 YEAR WARRANTY*

1 year warranty out of the box. Extra 2 years FREE with online registration at www.netcomm.com.au *Conditional upon registration online.

Your Netcomm dealer:

NetComm is Australia's dynamic data communications and networking solutions provider. For more information on this and other NetComm products, please visit www.netcomm.com.au

NetComm Limited ABN 85 002 490 486

PO Box 1200, Lane Cove NSW 2066 Australia.

PHONE (02) 9424 2070 • FAX (02) 9424 2010

www.netcomm.com.au • EMAIL sales@netcomm.com.au

Trademarks and registered trademarks are the property of NetComm Limited or their respective owners. Specifications are subject to change without notice. Images shown may vary slightly from the product.