



ADSL2+ Wireless Modem Router

4 Ethernet Ports with 11g Wireless and Firewall

RTA1025WE



FEATURES

- > Broadband Internet Access up to 24 Mbps
- > Supports ADSL, ADSL2 and ADSL2+
- > Simple Configuration
- > Integrated 54 Mbps Wireless Access
- > WirelessSecurity, WEP and WPA
- > 4 Ethernet Ports for Internet Sharing
- > Suitable for Home and Office Networks
- > Security Firewall & DMZ
- > VPN Passthrough
- > Port Forwarding, UPnP™ and QoS
- > Freecall Helpline



NZ (09) 448 5548
AUS (02) 9424 2000



12 MONTH
WARRANTY



www.dynalink.co.nz
www.dynalink.com.au

 **Dynalink**

Get Connected.

Technical Specifications (RTA1025WE)

ADSL Compliance

ADSL

- ANSI T1.413 Issue 2
- ITU G.992.1 Annex A (G.dmt)
- ITU G.992.2 Annex A (G.lite)
- ITU G.994.1 (G.hs)
- Support dying gasp
- Maximum Rate: 8 Mbps downstream and 1 Mbps upstream

ADSL2

- ITU G.992.3 Annex A (G.dmt)
- ITU G.992.4 Annex A (G.lite)
- Maximum Rate: 12 Mbps downstream and 1 Mbps upstream

ADSL2+

- ITU G.992.5 Annex A (G.dmt)
- Maximum Rate: 24 Mbps downstream and 1.2 Mbps upstream

ATM

- PPPoA (RFC 2364) and PPPoA Bridged mode
- PPPoE (RFC 2516) and PPPoE Bridged mode
- IPoA (RFC 2225)
- Bridged mode over AAL5 (RFC2684/1483)
- ATM Forum UNI 3.1 / 4.0 compliant PVCs
- UBR and CBR with traffic shaping
- OAM F4/F5 loopback cells

Bridging

- IEEE 802.1d self-learning bridge
- Learning up to 4096 MAC addresses
- Transparent Bridging between 10/100 Mb Ethernet

Routing

- NAT / PAT allows multiple users to share Internet access
- UPnP IGD with NAT traversal capability
- Port Forwarding: users can setup multiple virtual servers (e.g., Web, FTP, Mail servers) on the local network.
- Static routing & dynamic routing RIPv1/v2
- DNS Relay, Dynamic DNS
- DHCP Client/Relay/Server
- IGMP Proxy
- Support IP/Bridge QoS for different traffic classes
- Support reservation of bandwidth to guarantee voice quality of VoIP applications.

Security

- PAP, CHAP, and MS-CHAP for PPP authentication
- Firewall based on incoming & outgoing filtering of IP address/Port number/Protocol type
- Ping blocking from WAN
- DMZ hosting

Supported Applications

- Application Level Gateways preset for Auth/Ident, DNS, FTP, PPTP, IPSEC, POP3, SMTP, SSH, TELNET, TFTP & WEB servers. Multiple Virtual Servers can be setup in local network.
- VPN passthrough
- NetMeeting, MSN Messenger, FTP, Quick Time, mIRC, Real Player, CuSeeMe, online gaming.

Configuration and Management

- Embedded web configuration interface with password protection
- Remote management control
- Telnet session for local or remote management
- System events logging
- DSL connection diagnostics
- Firmware upgrade via web browser
- User setting backup & restore

Technical Specifications (RTA1025WE)

Hardware Interface

- One RJ-11 port for ADSL connection
- IEEE 802.11g and 802.11b Wireless LAN interface
- Four Ethernet ports for IEEE 802.3/802.3u 10/100 Base-T auto-sensing, auto cross-over
- One hidden reset button for restoring factory default settings

Chipset

- Broadcom BCM6348 single-chip ADSL2+ with integrated MIPS32 CPU, transceiver & Analog Front End
- Broadcom BCM4318 single-chip 802.11g wireless LAN solution

Wireless LAN

- Supports IEEE 802.11g and 802.11b
- Data Rates: 54, 48, 36, 24, 18, 12, 9, 6 Mbps for 802.11g and 11, 5.5, 2, 1 Mbps for 802.11b
- Diversity antenna system: one external antenna and one internal antenna
- Maximum RF output power: 15dBm for 802.11g
- Coverage Area:
 - 802.11g: LOS (Outdoors): Max. 50 meters;
 - Indoors: Max. 20 meters
 - 802.11b: LOS (Outdoors): Max. 180 meters;
 - Indoors: Max. 60 meters
- Support WEP (Wired Equivalent Privacy) RC4 with 64-bit or 128-bit key length
- Support Access Control List, only registered WLAN clients are allowed
- Support 802.1x, WPA-PSK, WPA, WPA2 & Mixed WAP/WPA2. Support SS ID stealthing
- Support repeater function to extend coverage
- Support client isolation for wireless hotspot
- Support SS ID stealthing

Regulatory Approval and Compliance


- ACA
- Telecom New Zealand PTC270

Power Requirement and Operation Environment Requirement


- Power Adaptor: Output 12 VAC, 1A
- Power Consumption: less than 10 W
- Ambient Temperature: 0 to 40°C
- Relative Humidity: 20% to 90% (non-condensing)

Physical

- Front Panel: 9 LED Indicators



- Back Panel



- Dimensions: 190mm(L) x 130mm(W) x 40mm(H)
- Weight: 350g

