



5 Port Ethernet Switch

Superfast 10/100 Mbps Ethernet Switch

SH9005A



FEATURES

- > Offers guaranteed bandwidth per port
- > Auto-negotiation half/full-duplex 10/100Mbps
- > Auto MDI/MDIX eliminates the need for crossover cables
- > Store-and-forward switching ensures corrupt frames are not forwarded
- > Proprietary backpressure flow control in half-duplex mode. Holds off transmission until backlogged traffic has been cleared
- > Metal case



NZ 0800 653 962
AUS 1800 063 962



12 MONTH
WARRANTY



www.dynalink.co.nz
www.dynalink.com.au



Get Connected.

Technical Specifications (SH9005A)

| | |
|--------------------------------|--|
| Standards | IEEE 802.3 (10Base-T) IEEE 802.3u (100Base-TX) |
| LAN Ports | 5 ports RJ45, auto MDI/MDIX |
| Transmission | Auto-negotiation, half/full-duplex, 10/100Mbps |
| Flow Control | Full duplex: IEEE 802.3x Half duplex: back pressure |
| Switching Method | Store-and-forward |
| Buffer Size | 1M bit |
| MAC Address Table | 1k entries |
| Maximum Filtering Rate | 148,800 packets per second |
| Maximum Forwarding Rate | 148,800 packets per second |
| Indicators | Power, Link/Activity, Speed |
| Power Input | DC 12V 0.5A external power adaptor |
| Operating Environment | 0 - 50°C, 10 - 90% humidity non-condensing |
| Mounting Method | Desktop |
| Dimensions | 127 x 83 x 30mm |

